

LPG Safety and Training Record Form

This form is intended to provide a safety training talk for staff at sites where LPG is used and a LCC is required but staff do not access the LPG cylinders other than to change the supply from one manifold to the next. All other gas connection/disconnection work for the site is undertaken by the gas supply company.

Please fill in your site details and provide a copy of the completed form (with training details signed) to Chemsafety.

LPG Location Details	
Con County Commons Counts at	
Gas Supply Company Contact Details	
Gas Fitter Contact Details	
Gas Fitter Contact Details	
The Hazards of LPG	LPG is a very flammable gas.
	LPG is easily ignited by flames, sparks or hot surfaces.
	LPG is heavier than air and can build up in confined areas causing a suffocation hazard
	as well as a fire hazard.
2	LPG can cause cold burns if it touches your skin
	Breathing in LPG will make you feel dizzy, nauseous/sick and can cause you to pass
	out or even die.
	LPG has an odour added to it so you can smell it.
LPG Safety	The LPG cylinder cage must be kept locked at all times
	Staff should only need to access the cylinders to turn the supply valve. Only
	personnel trained in gas safety should do this.
	DO NOT disconnect any of the hoses.
	DO wear safety glasses when turning the supply valve.
The Safety Data Sheet for	
LPG is located:	
The Emergency Response	
Plan is located:	
	If you smell gas at the cylinder store
	If it is safe to do so, CLOSE the isolation valves and/or cylinder valves,
	Contact your supplier immediately
	Secure the area around the gas cylinders and keep it clear until the issue is fixed.
	If you smell gas in the building TURN-OFF the supply and contact a gas fitter or gas
	appliance servicing agency immediately.
	Do not operate any electrical switches.
	Open windows and doors to ventilate the area
Emarganar Stan / Indiation	Evacuate the building
Emergency Stop / Isolation Valves are located:	
Gas Fire	In the event of a gas fire call Fire and Emergency NZ immediately on 111
Gastile	If safe to do so, turn-off the gas supply
	Do not extinguish the fire unless the gas flow can be shut off
	Evacuate to a safe location upwind from the fire
Obligations under the HSW-	Workers must take reasonable care of their own health and safety. You must comply
Act	with health and safety policy and procedures and any reasonable request made by
	the person in charge relating to health and safety. If issued with personal protective
	equipment, you must wear it as directed and ensure it is maintained or replaced as
	required.
	required.

Training Records

This form is intended to be used as a safety briefing for LPG where the use of the gas is limited to changing the supply valve over from one bank of cylinder to the next. Use the first page of this form as a staff safety briefing, either individually or in a group.

Go over each section of the table above so that all staff are aware of the hazards of LPG, basic safety procedures and the location of safety data sheets on site.

Each staff member should sign this form to indicate that that have been part of this training. Print off as many copies of page 3 as you need to cover your team.

Name Role/Job Description	Signature of Staff Member	Date of Training	Training Method
			☐ I have read this safety information
			☐ Safety Talk given by: Name: Role:
			☐ I have read this safety information ☐ Safety Talk given by: Name: Role:

Name	Signature of Staff Member	Date of Training	Training Method
Role/Job Description			
			☐ I have read this safety information
			☐ Safety Talk given by:
			Name:
			Role:
			☐ I have read this safety information
			☐ Safety Talk given by:
			Name:
			Role:
			Note:
			☐ I have read this safety information
			☐ Safety Talk given by:
			Name:
			Role:
			☐ I have read this safety information
			☐ Safety Talk given by:
			Name:
			Role: